

Laser-driven generation of collimated quasi-monoenergetic proton beam using double-layer target with interface modulations

2D PIC simulation of high-intensity laser pulse and double-layer deuterium-hydrogen target with modulated interface. The laser pulse (green color in the video) initiates instability on the interface between deuterium (blue) and proton (purple to yellow) layers. It results in generation of collimated quasi-monoenergetic proton bunch of high energy (yellow).

With the advent of multi-petawatt laser systems like the ELI-Beamlines (Czech Republic), APOLLON (France) and SEL (China) the laser-driven ion accelerators will enter the acceleration regimes dominated by radiation pressure [1]. High quality ion beams with low emittance and narrow energy spectrum will be generated when these lasers irradiate tailored targets.

Pre-modulated targets can undergo relativistic Rayleigh-Taylor and Richtmyer-Meshkov like instabilities, which can improve the properties of generated ion beams [2,3].

We study the effects of the interface modulations in double-layer targets with 2D numerical particle-in-cell (PIC) simulations using the code EPOCH [4].

The target consists of deuterium (blue color scale in the video) and proton (purple to yellow scale) layers. The color scales also denote the local mean energy of the respective ion particles. The vertical height represents their local density. The electric field of linearly s-polarized (electric field is perpendicular to the plane of incidence) Gaussian laser pulse is represented by both the vertical height and by the green scale.

Small perturbations originated from the interface modulation grow during the laser-target interaction. This leads to the formation of low-density regions and high-density ion bunches between them at the positions determined by the pre-modulation geometry. The ion bunches are then accelerated by the laser radiation pressure. The collimated central bunch of proton beam has the average energy in the multi-GeV range with narrow energy spread. The laser accelerated ion beams from composite targets may also find applications in material sciences and nuclear physics research [5]. Further information can be provided during the poster presentation P1.2007 and in the corresponding EPS conference paper [6].

Our work was supported by projects HIFI (CZ.02.1.01/0.0/0.0/15_003/0000449) and ELITAS (CZ.02.1.01/0.0/0.0/16_013/0001793) from the ERDF and by CSF project 18-09560S. computer resources for simulations were provided by IT4Innovations (LM2015070).

The video was produced in collaboration with our colleagues from the Virtual Beamline (VBL) team at ELI-Beamlines.

REFERENCES

- [1] T. Esirkepov, M. Borghesi, S. V. Bulanov et al., Phys. Rev. Lett. 92, 175003 (2004)
- [2] F. Pegoraro and S. V. Bulanov, Phys. Rev. Lett. 99, 065002 (2007)
- [3] S. V. Bulanov, E. Y. Echkina, T. Z. Esirkepov et al, Phys. Rev. Lett. 104, 135003 (2010)
- [4] T. D. Arber, K. Bennett, C. S. Brady et al., Plasma Phys. Control. Fusion 57, 113001 (2015)
- [5] M. Nishiuchi, H. Sakaki, T. Z. Esirkepov et al., Physics of Plasmas 22, 033107 (2015).
- [6] M. Matys, K. Nishihara, M. Kecova et al., 46th EPS Conference on Plasma Physics, P1.2007 (2019)

AUTHORS & CONTACT INFORMATION

Name (first/last): Martin Matys, Mariana Kecova, Katsunobu Nishihara, Jan Psikal, Georg Korn & Sergei V. Bulanov
Affiliation(s): ELI-Beamlines project, Institute of Physics, Czech Academy of Sciences, Czech Republic
Email: Martin.Matys@eli-beams.eu